



Large Format Displays

Sleek, slim, stylish 4K professional displays with maximum visual impact for your signage experience

4K

4K ultra HD resolution

The Sedao LFD delivers the ultimate sharp, clear and precise definition ensuring your engagement with your audience is a vivid signage experience.




5 year de-install and re-install warranty

This unique market warranty adds extra value to your investment giving you the confidence of knowing your screen has a 5 year option.



16/7 operation

16 hours playout a day providing you with the flexibility to allocate and display your screen/s in places that are open for long periods of time.



Landscape & portrait

Dual orientation versatility enabling you to create engaging content to suit the location of the screen installation.



USB media playback

This USB feature offers a simple way to playout photos and videos in a slideshow with autoplay or manual operation.



OPS PC slot*

OPS Slot allows for connection of any Open Pluggable Specification module to add built in computing capabilities to the panel.



Removable logo

The removable logo ensures your message is surrounded by a sleek and stylish frame without additional branding to detract from the display on the screen.



Power management scheduling

Be environmentally friendly and reduce energy consumption using the power management scheduling feature to start up and shut down during operational periods only.

PANEL				
Diagonal Screen Size (inches)	49"	55"	65"	75"
Panel Technology	IPS, Edge LED	IPS, Edge LED	VA, Direct LED	IPS, Edge LED
Maximum Daily Usage Hours	16/7	16/7	16/7	24/7
Display Colours	8 Bit, 16.7 M Colors	8 Bit, 16.7 M Colors	8 Bit, 16.7 M Colors	10bit(D), 1.07 Billion colours
Orientation	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait	Landscape/Portrait
Viewing Angle	178°	178°	178°	178°
Brightness (Cd/m2)	400	400	400	400
Panel Life Time (Typ.) (Hr)	30000	30000	30000	50000
Response Time (ms)	6	9	6.5	8
H-Freq (KHz)	67.5	67.5	135	135
V-Freq (Hz)	60	60	120	60
INPUTS				
HDMI 2.0 support	2	2	2	2
VGA	✓	✓	✓	✓
USB 2.0	2 (1 x internal)	2 (1 x internal)	2 (1 x internal)	2 (1 x internal)
USB 3.0	1	1	1	1
USB Support Type	Photo/Video/MP3 with autoplay	Photo/Video/MP3 with autoplay	Photo/Video/MP3 with autoplay	Photo/Video/MP3 with autoplay
RS232	9 pin DSUB	9 pin DSUB	9 pin DSUB	9 pin DSUB
LAN (RJ45)	✓	✓	✓	✓
YPbPr	✓	✓	✓	✓
Audio (Twin Phono)	✓	✓	✓	✓
SUPPORTED INPUT RESOLUTIONS				
HDMI	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160
VGA (D-Sub)	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080
OUTPUTS				
HDMI	✓	✓	✓	✓
Mini Jack (Audio)	✓	✓	✓	✓
RCA (L/R)	✓	✓	✓	✓
Speakers (W)	2X8	2X8	2X8	2X12
Headphone	✓	✓	✓	✓
FEATURES				
Daisy Chain HDMI I/O	✓	✓	✓	✓
UHD Daisychaining	✓	✓	✓	✓
Wireless (2.4GHz / 5GHz)	✓ (802.11 a/b/g/n support)	✓ (802.11 a/b/g/n support)	✓ (802.11 a/b/g/n support)	✓ (802.11 a/b/g/n support)
OPS Slot	✓	✓	✓	✓
Built in Scheduler	✓	✓	✓	✓
Real time clock	Manual/Network/No backup/NTP	Manual/Network/No backup/NTP	Manual/Network/No backup/NTP	Manual/Network/No backup/NTP
CEC	✓	✓	✓	✓
ARC	✓	✓	✓	✓
POWER				
Power Supply	110 VAC - 240 VAC - 50/60 Hz	110 VAC - 240 VAC - 50/60 Hz	110 VAC - 240 VAC - 50/60 Hz	110 VAC - 240 VAC - 50/60 Hz
Avg on mode (W)	78	79	118	244
Active Standby Consumption (W)	17.35	17.35	13.61	22.61
Standby Consumption (Wz)	≤0.5	≤0.5	≤0.5	≤0.5
OPERATION				
Temperature Conditions (°C)	0 – 40	0 – 40	0 – 40	0 – 40
Humidity (%)	0 – 90	20 – 80	0 – 90	20 – 80
MECHANICAL				
Product Dimensions (mm) (WxDxH)	1097 x 630 x 69	1236 x 709 x 69	1459 x 841 x 96	1684 x 967 x 100
Product Weight (kg)	15.7	22	25.6	37
Bezel Width (mm)	8 (T/L/R) 12 (B)	9.5 (T/L/R) 11 (B)	15 (T/L/R) 21 (B)	16 (T/L/R) 23 (B)
Package Dimensions (mm) (WxHxD)	1215 x 775 x 165	1340 x 870 x 170	1620 x 1006 x 190	1948 x 1170 x 210
Package Weight (kg)	20.15	31.5	33.5	52
Vesa Mounting (mm)	200 x 200	400 x 400	400 x 400	600 x 400